

# Peli protector cases – Protector transport cases – 1650 case



## 1650 Case

### Interior dimensions:

72.4 x 44.1 x 26.7 cm  
(28.50" x 17.37" x 10.50" )

**This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application**

- **Watertight, crushproof, and dust proof**
- Easy-open, double-step latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel hardware and padlock protectors
- 2 layer Pick 'N' Pluck™ foam with convoluted lid foam
- Personalised nameplate service available
- Unconditionally Guaranteed
- **Retractable extension handle**
- **4 strong polyurethane wheels with stainless steel bearings**



Black

## Configurations

Cat. #	Description
1650	1650 Case (with foam)
1650NF	1650 Case (no foam)
1654	1650 Case with Padded Dividers

## 1650 Case Specifications

### Exterior Dimensions

(L x W x D)  
78.1 x 52 x 29.5 cm  
(30.75" x 20.50" x 11.62")

### Interior Dimensions

(L x W x D)  
72.4 x 44.1 x 26.7 cm  
(28.50" x 17.37" x 10.50")

**This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.**

### Lid Depth

4.7 cm  
(1.87")

### Bottom Depth

21.9 cm  
(8.62")

### Total Depth

26.6 cm  
(10.49")

### Weight w/Foam

16.1 kg.  
(35.49 lbs)

### Weight w/o Foam

13.2kg  
(29.1 lbs.)

### Buoyancy Max.

82.1 kg  
(181 lbs. )

### Range Temperature

-23 / 99° C  
(-10 / 210° F)

### No. of Wheels

4

Personalized Nameplate Available

## 1650 Case Certificates

• IP67(1 meter submersion for 30 minutes) • MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

## 1650 Case Accessories

Cat. #	Description
1651	4 pc. Replacement Foam Set
1655	Padded Divider Set Only
1659	Photo/Lid Organizer for 1650 Case